

**OPP WHITE GLOSS TC 60 µm – REMOVABLE –  
KRAFT 135gsm**

Issue: 28/05/2011  
Modification: 3  
page 1/1

**GENERAL PRODUCT CHARACTERISTICS**

Total weight	210 gsm ± 6%	ISO 536
Total caliper	203 µm ± 6%	ISO 534

**FACE:**

Bi-axially oriented polypropylene film, white gloss, with a print-receptive Top Coating

Substance	59 gsm ± 3	-
Caliper	60 µm ± 2	-

**ADHESIVE**

Water emulsion removable adhesive type, good short and long-term removability from most substrates including processed board, glass, steel and polyolefin films.

Peel adhesion	0,6 N/inch ± 0,2	FINAT1
Shear test	6h ± 2	FINAT8
Quick stick	0,7 N/inch ± 0,2	FINAT9
Min. application temp.	- 5°C / +50°C	
Service temp. Range	-20°C/+60°C	

**BACKING**

One-side coated white kraft, solventless silicon coated

Substance	135 gsm ± 7	ISO 536
Caliper	130 µm ± 8	ISO 534

**SAFETY REGULATIONS**

The self-adhesive product meets the European Standard EN71-3:2013 "Safety of Toys" - Migration of certain elements

**APPLICATIONS**

Hi-quality labels for cosmetics, appliances and toys; for the furniture and vehicle industry, promotional and decorative labels for indoor and outdoor use. Good dimensional stability and ageing resistance. NB. the removing properties are influenced by the kind of application surface. Trials are recommended, by the purchaser, prior to use, on the intended substrates for product suitability. Not suitable for application on paper surfaces.

**PRINTABILITY**

Face: screen-and flexo printing, conventional and UV- offset printing using suitable inks. Consult your inks supplier about suitable printing inks to obtain maximum ink bonding  
Backing: good printing results by all common print processes, in one or more colors

**ON REQUEST**

FSC Forest Stewardship Council certified material.  
Splits on the release paper, standard spacing 38mm or customized.

**SHELF LIFE AND USE**

Two (2) years from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C.
- Relative Humidity 45% - 60%.
- Store in a cool dry place.
- Store away from heaters or direct sunlight or rain.
- Keep the sheets flat, the reels piled.
- Store in the original packaging.  
Store in the original packaging, remove packaging just before use.
- Material to be acclimatized at least 24 hrs to ambient conditions.