Technical Data Sheet

Issue: 24/11/2015 Modification: 0

page 1/1



Double-Sided Adhesive - white glassine paper Core Supertack - Kraft 85gsm

GENERAL PRODUCT CHARACTERISTICS

Total weight	268gsm ± 5%	ISO 536		
Total caliper	254µm ± 6%	ISO 534		

Double sided adhesive construction with white glassine paper 62 gsm core and liner on both sides

CORE

White glassine paper core 62 gsm with adhesive coating on both sides

Substance	62gsm ± 2	ISO 536
Caliper	54 µm ± 3	ISO 534

ADHESIVE

DOUBLE-SIDED ADHESIVE COATED

Water emulsion acrylic based Extra-Permanent type, high initial tack and strong permanent bond. Recommended for application on a wide variety of substrates, like paper, board, glass, steel.

Peel adhesion	16,5N/inch ± 2	FINAT1
Shear test	4h ± 2	FINAT8
Quick stick	14,4 N/inch ± 4	FINAT9
Application temp.	+5°C/+40°C	
Service temp. Range	-20°C/+90°C	

The adhesive complies with FDA 175.105 and BfR XIV Regulations for contact with foodstuffs. The product meets the European Toy Regulation EN 71/3

BACKING

One-side coated white kraft; solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

The product meets the European Toy Regulation EN 71/3

APPLICATIONS

BRICOLAGE, SAMPLE-BOOKS, PHOTO ALBUMS, CHARTS Tests for suitability, prior to use, are always recommended.

PRINTABILITY

Backing: good printing results by all common print processes, in one or more colors

SHELF LIFE AND USE

3 (three) years from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% 60%

• Store in a cool dry place away from heaters or direct sunlight or rain

- Keep the sheets flat, the reels piled
- Store in the original packaging

All technical data are subject to change without prior notice.

ITALSTICK Soc. Coop. via della Stazione, 6 I-41019 Soliera www.italstick.com Ph. +39 059 566705 Fax +39 059 565127 info@italstick.com

All ITALSTICK products are subject to careful quality control throughout the production process and are warranted to be free from manufacturing defect and of quality. The reported information is based upon research and tests the Company believes to be reliable; such information does not constitute a warranty. The purchaser and/or user should carefully test, prior to use, suitability and performance of the product for the intended use and shall assume all risks for such use. ITALSTICK shall not be liable for damages beyond the replacement value of the defected product nor for incidental or consequential damages