

ITALW LAID PAPER IVORY 85gsm – SUPERTACK PLUS – KRAFT 85gsm

Issue: 22/09/2021
Last Modification: -
Revision.: 0
Pag 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	192 gsm $\pm$ 5%	ISO 536
Total caliper	208 μ m $\pm$ 6%	ISO 534

FACE

Paper realized with ECF (Elementary Chlorine Free) wood-free primary Pulp. High wet strength level, "anti-splatter". Neutral pH.

Substance	85 gsm $\pm$ 4	ISO 536
Caliper	106 μ m $\pm$ 5	ISO 534

ADHESIVE

Water emulsion, styrene-acrylic based Extra-Permanent type, tackified. High initial tack. Suitable for applications on a wide variety of substrates such as papers, boards, glass, steel and difficult surfaces such as apolar, rough, curved surfaces.

Recommended for application on glass bottles where durable labels are required. Good adhesion on humid and cold surfaces, good resistance after immersion in ice water.

Peel adhesion	16.5 N/inch $\pm$ 2	FINAT1
Shear test	4h $\pm$ 2	FINAT8
Quick stick	14,3 N/inch $\pm$ 4	FINAT9
Min. Application temp.	-10°C	
Service temp. Range	-15°C / +80°C	

BACKING

Clay coated kraft white, solventless silicon coated.

Substance	85 gsm $\pm$ 3	ISO 536
Caliper	87 μ m $\pm$ 5	ISO 534

SAFETY REGULATIONS

- The Adhesive Coating: in accordance with FDA 21 CFR 175.105
- Adhesives- and in accordance with EU Regulation N°10/2011
- APEO Free and Phthalate Free

APPLICATIONS

High quality labels especially created for the labeling of wine and spirit bottles. The excellent water resistance property makes the self-adhesive product suitable for immersing bottles in ice water.
Not suited for bottle neck labels.

Trials are recommended, by the purchaser, on the intended substrates, prior to use, for product suitability.

PRINTABILITY

Face: excellent printing results by all main printing processes, litho, flexo, offset, screen printing and hot-stamping. Printing tests prior to use are always recommended.

Backing: good printing results by all common print processes, in one or more colors.

ON REQUEST

- Backing paper with splits each 38 mm. or customized
- Material certified Forest Stewardship Council® FSC-C107414

SHELF LIFE AND USE

One (1) year from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging, remove packaging just before use
- Material to be acclimatized at least 24 hours to ambient conditions