

ITALW LAID PAPER EXTRA WHITE WS – SUPERTACK PLUS - KRAFT 85 GSM

Issue: 14/09/2023
Last modification: 24/03/2025
Revision.: 1
Pag 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	197 gsm $\pm$ 5%	ISO 536
Total caliper	222 μ m $\pm$ 6%	ISO 534

FACE

Laid paper extra white, classic texture, realized with pure cellulose ECF (Elementary Chlorine Free) wood-free primary Pulp, from properly managed forests. Good Wet Strength, neutral pH

Substance	90gsm $\pm$ 4	ISO 536
Caliper	120 μ m $\pm$ 6	ISO 534

ADHESIVE

Water emulsion, styrene-acrylic based, Extra -Permanent type, tackified. High initial tack. Suitable for applications on a wide variety of substrates such as papers, boards, glass, steel and difficult surfaces e.g. apolar, rough, curved surfaces. Recommended for application on glass bottles where durable labels are required. Good adhesion on humid and cold surfaces, good resistance to immersion in water/ice.

Peel adhesion	16.5 N/inch $\pm$ 2	FINAT1
Shear test	4h $\pm$ 2	FINAT8
Quick stick	14.3 N/inch $\pm$ 4	FINAT9
Min. application temp.	-10°C	
Service temp. Range	-15°C/+60°C	

BACKING

Clay coated kraft white, solventless silicon coated.

Substance	85 gsm $\pm$ 3	ISO 536
Caliper	87 μ m $\pm$ 5	ISO 534

SAFETY REGULATIONS

The adhesive coating does comply with FDA 21 CFR 175.105 "Adhesives" in conformity with the Regulation (EU) N. 10/2011 APEO-free / Phthalate-free

APPLICATIONS

High quality labels especially created for the labeling of wine and spirit bottles.

Trials are recommended, by the purchaser, on the intended substrates, prior to use, for product suitability.

PRINTABILITY

Face: excellent printing results by all main print processes, litho, flexo, offset, screen printing and hot-stamping. Printing tests prior to use are always recommended..

Backing: good printing results by all common print processes, in one or more colors.

ON REQUEST

- backing paper with splits each 38 mm. or customized
- material certified Forest Stewardship Council® FSC-C107414

SHELF LIFE AND USE

One (1) year from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging, remove packaging just before use
- Material to be acclimatized at least 24 hrs to ambient conditions