

**ALUMINIUM FOIL matt silver 72gsm – SUPERTACK  
KRAFT 85 GSM**

Issue: 08/04/2016  
Modification: 0  
page 1/1

**GENERAL PRODUCT CHARACTERISTICS**

Total weight	177 gsm ± 6%	ISO 536
Total caliper	162µm ± 9%	ISO 534

**FACE:**

Matt silver aluminium foil, top coated, laminated on woodfree paper

Substance	72 gsm ± 4	ISO 536
Caliper	60 µm ± 6	ISO 534

**ADHESIVE**

Water emulsion acrylic based supertack type, high initial tack and strong permanent bond for general use. Recommended on a wide variety of substrates, like paper, board, glass, steel

Peel adhesion	16,5N/inch ± 2	FINAT1
Shear test	4h ± 2	FINAT8
Quick stick	14,4 N/inch ± 4	FINAT9
Application temp.	+5°C/+40°C	
Service temp. Range	-20°C/+90°C	

**BACKING**

One-side coated white kraft, solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

**SAFETY REGULATIONS**

The adhesive coating complies with FDA 21 CFR 175.105 for contact with foodstuffs and meets EN71-3:2013 "Safety of Toys" – Migration of certain elements

The backing paper meets EN71-3:2013 "Safety of Toys" – Migration of certain elements

**APPLICATIONS**

High quality labels for cosmetics, confectionery, spirits and beverages, toiletries, and electronics. Trials are recommended, by the purchaser, on the intended substrates, prior to use, for product suitability.

**PRINTABILITY**

Face: primer-coated for offset printing, litho, letterpress and silk-screen printable. Fast drying inks recommended. Consult your inks supplier about suitable printing inks to obtain maximum printing results.

Backing: good printing results by all common print processes, in one or more colours

**ON REQUEST**

Forest Stewardship Council (FSC) certified material.

Splits on the release paper, standard spacing 38mm or customized

**SHELF LIFE AND USE**

Three (3) years from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging

All ITALSTICK products are subject to careful quality control throughout the production process and are warranted to be free from manufacturing defect and of quality. The reported information is based upon research and tests the Company believes to be reliable; such information does not constitute a warranty. The purchaser and/or user should carefully test, prior to use, suitability and performance of the product for the intended use and shall assume all risks for such use. ITALSTICK shall not be liable for damages beyond the replacement value of the defected product nor for incidental or consequential damages

All technical data are subject to change without prior notice.

**ITALSTICK Soc. Coop.**  
via della Stazione, 6  
I-41019 Soliera  
www.italstick.com

Ph. +39 059 566705  
Fax +39 059 565127  
info@italstick.com