

# SEMI-GLOSS MC 80gsm OPAQUE - AD05-KRAFT K85

Issue: 10/02/2012

Modification: 0

page 1/1

## **GENERAL PRODUCT CHARACTERISTICS**

Total weight 185gsm  $\pm$  5% ISO 536 Total caliper 175 $\mu$ m  $\pm$  6% ISO 534

## **FACE**

White semi-gloss coated woodfree paper, opaque

Substance  $80 \text{gsm} \pm 2$  ISO 536 Caliper  $73 \mu \text{m} \pm 2$  ISO 534

The product meets the European Toy Regulation EN71/3

# **ADHESIVE**

Water emulsion acrylic based Extra-Permanent type, high initial tack and strong permanent bond for general use. Very good adhesion on a wide variety of substrates, like paper, board, glass, steel

Peel adhesion 16,5N/inch  $\pm$  2 FINAT1 Shear test 4h  $\pm$  2 FINAT8 Quick stick 14,4 N/inch  $\pm$  4 FINAT9

Application temp. -5°C/+40°C Service temp. Range -15°C/+80°C

The adhesive complies with FDA 175.105 and BfR XIV regulations, for contact with foodstuffs.

The product meets the European Toy Regulation EN71/3

#### BACKING

One-side coated white kraft; solventless silicon coated

Substance 85 gsm  $\pm$  3 ISO 536 Caliper 87  $\mu$ m  $\pm$  5 ISO 534

The product meets the European Toy Regulation EN71/3

## **APPLICATIONS**

High opacity labels for covering undesired text or printed surfaces, cover-up labels.

Suitable for application on flat and curved substrates, small to medium diameter.

# **PRINTABILITY**

Face: excellent printing results by all common print processes, particularly using brilliant inks.

Backing: good printing results by all common print processes, in one or more colors

# SHELF LIFE AND USE

Three (3) years from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging