White Offset 80gsm - SUPERTACK AD05 - KRAFT 85gsm

Issue: 14/10/2011 Modification: 0 page 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight 185gsm \pm 6% ISO 536 Total caliper 206 μ m \pm 6% ISO 534

FACE

White woodfree uncoated paper, high whiteness and opacity

Substance 80gsm \pm 4 ISO 536 Caliper 104 μ m \pm 4 ISO 534

The product meets the European Toy Regulation EN 71/3

ADHESIVE

Water emulsion acrylic based Extra-Permanent type, high initial tack and strong permanent bond for general use. Very good adhesion on a wide variety of substrates, like paper, board, glass, steel.

 $\begin{array}{lll} \mbox{Peel adhesion} & \mbox{16,5N/inch} \pm 2 & \mbox{FINAT1} \\ \mbox{Shear test} & \mbox{4h} \pm 2 & \mbox{FINAT8} \\ \mbox{Quick stick} & \mbox{14,4 N/inch} \pm 4 & \mbox{FINAT9} \\ \end{array}$

Application temp. +5°C/+40°C Service temp. Range -15°C/+80°C

The adhesive complies with FDA 175.105 and BfR XIV regulations for contact with foodstuffs.

The product meets the European Toy Regulation EN 71/3

BACKING

One-side coated white kraft; solventless silicon coated

Substance 85 gsm \pm 3 ISO 536 Caliper 87 μ m \pm 5 ISO 534

The product meets the European Toy Regulation EN71/3

APPLICATIONS

All types of labels for industrial applications: information and product labeling.

PRINTABILITY

Face: good printing results by all common print processes; suitable for laser and ink-jet printing Backing: good printing results by all common print processes, in one or more colors.

SHELF LIFE AND USE

One (1) year from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% 60%
- Store in a cool dry place away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging

All SAM UK Ltd products are subject to careful quality control throughout the production process and are warranted to be free from manufacturing defect and of quality. The reported information is based upon research and tests the Company believes to be reliable; such information does not constitute a warranty. The purchaser and/or user should carefully test, prior to use, suitability and performance of the product for the intended use and shall assume all risks for such use. SAM UK Ltd shall not be liable for damages beyond the replacement value of the defected product nor for incidental or consequential damages