

**Double-Sided Adhesive - white glassine paper Core
Supertack - Kraft 85gsm**

Issue: 24/11/2015
Modification: 0
page 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	268gsm ± 5%	ISO 536
Total caliper	254µm ± 6%	ISO 534

Double sided adhesive construction with white glassine paper 62 gsm core and liner on both sides

CORE

White glassine paper core 62 gsm with adhesive coating on both sides

Substance	62gsm ± 2	ISO 536
Caliper	54 µm ± 3	ISO 534

ADHESIVE

DOUBLE-SIDED ADHESIVE COATED

Water emulsion acrylic based Extra-Permanent type, high initial tack and strong permanent bond. Recommended for application on a wide variety of substrates, like paper, board, glass, steel.

Peel adhesion	16,5N/inch ± 2	FINAT1
Shear test	4h ± 2	FINAT8
Quick stick	14,4 N/inch ± 4	FINAT9
Application temp.	+5°C/+40°C	
Service temp. Range	-20°C/+90°C	

The adhesive complies with FDA 175.105 and BfR XIV Regulations for contact with foodstuffs. The product meets the European Toy Regulation EN 71/3

BACKING

One-side coated white kraft; solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

The product meets the European Toy Regulation EN 71/3

APPLICATIONS

BRICOLAGE, SAMPLE-BOOKS, PHOTO ALBUMS, CHARTS
Tests for suitability, prior to use, are always recommended.

PRINTABILITY

Backing: good printing results by all common print processes, in one or more colors

SHELF LIFE AND USE

3 (three) years from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging