

**Double-Sided Adhesive clear Polypropylene 35my Core  
Supertack - Kraft 85gsm**

Issue: 04/12/2013  
Modification: 2  
page 1/1

**GENERAL PRODUCT CHARACTERISTICS**

Total weight	238gsm ± 6%	ISO 536
Total caliper	235µm ± 8%	ISO 534

Double sided adhesive construction with clear polypropylene 35my core, and liner on both sides

**CORE**

Clear gloss polypropylene core with adhesive coating on the two sides

Substance	32gsm ± 2	ISO 536
Caliper	35 µm ± 3	ISO 534

**ADHESIVE**

**DOUBLE-SIDED ADHESIVE COATED**

Water emulsion acrylic based Extra-Permanent type, high initial tack and strong permanent bond. Recommended for application on a wide variety of substrates, like paper, board, glass, steel.

Peel adhesion	16,5N/inch ± 2	FINAT1
Shear test	4h ± 2	FINAT8
Quick stick	14,4 N/inch ± 4	FINAT9
Application temp.	+5°C/+40°C	
Service temp. Range	-20°C/+90°C	

The adhesive complies with FDA 175.105 and BfR XIV Regulations for contact with foodstuffs. The product meets the European Toy Regulation EN 71/3

**BACKING**

One-side coated white kraft; solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

The product meets the European Toy Regulation EN 71/3

**APPLICATIONS**

BRICOLAGE, SAMPLE-BOOKS, PHOTO ALBUMS, CHARTS  
Tests for suitability, prior to use, are always recommended.

**PRINTABILITY**

Backing: good printing results by all common print processes, in one or more colors

**SHELF LIFE AND USE**

3 (three) years from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging