

Uncoated Board 170 gsm – Supertack – kraft 85gsm

Issue: 05/09/2011
Modification: 3
page 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	279gsm ± 5%	ISO 536
Total caliper	301µm ± 6%	ISO 534

FACE

White woodfree uncoated paper

Substance	170gsm ± 7	ISO 536
Caliper	187µm ± 8	ISO 534

ADHESIVE

Water emulsion acrylic based Supertack type, high initial tack and strong permanent bond. Very good adhesion on a wide variety of substrates, like paper, board, glass, steel.

Peel adhesion	16,5N/inch ± 2	FINAT1
Shear test	4h ± 2	FINAT8
Quick stick	14,4 N/inch ± 4	FINAT9
Application temp.	+5°C/+40°C	
Service temp. Range	-20°C/+90°C	

The adhesive complies with FDA 175.105 and BfR XIV regulations for contact with foodstuffs.
The product meets the European Toy Regulation EN 71/3

BACKING

One-side coated white kraft; solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

The product meets the European Toy Regulation EN71/3

APPLICATIONS

Identification labels, postcards and promotional tags . Any application where high stiffness and thickness are required.

PRINTABILITY

Face: excellent printing results by all common print processes, in one or more colors
Backing: good printing results by all common print processes, in one or more colors.

SHELF LIFE AND USE

One (1) year from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging