

GLOSS MC 80gsm – AD06 – KRAFT 85

Issue: 19/09/2011
Modification: 1
page 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	183 gsm ± 6%	ISO 536
Total caliper	164 µm ± 7%	ISO 534

FACE:

White gloss double coated woodfree paper.

Substance	80 gsm ± 3	ISO 536
Caliper	64 µm ± 4	ISO 534

The product meets the European Toy Regulation EN71/3

ADHESIVE

Water emulsion removable adhesive type, good short and long-term removability from most substrates including processed board, glass, steel and polyolefin films.

Peel adhesion	0.8 N/inch ± 0.2	FINAT1
Shear test	6h ± 2	FINAT8
Quick stick	0.7 N/inch ± 0.2	FINAT9
Min. application temp.	+5°C / +50°C	
Service temp. Range	-20°C/+60°C	

The product meets the European Toy Regulation EN71/3

BACKING

One-side coated white kraft; solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87µm ± 5	ISO 534

The product meets the European Toy Regulation EN71/3

APPLICATIONS

High quality multicolor labels. Good print definition and finishing: decorative labels, advertising, promotion labels, for cosmetic and pharmaceutical industry. NB. the removing properties are influenced by the kind of application surface. Trials are recommended, by the purchaser, prior to use, on the intended substrates. Not suitable for application on papers.

PRINTABILITY

Face: good printing results by all common print processes, excellent results using brilliant inks
Backing: good printing results by all common print processes, in one or more colours.

SHELF LIFE AND USE

Two (2) years from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place
- Store away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging