

White offset 80gsm – AD06 – KRAFT 85gsm

Issue: 17/07/2013
Modification: 0
page 1/1

GENERAL PRODUCT CHARACTERISTICS

Total weight	183gsm ± 6%	ISO 536
Total caliper	204µm ± 6%	ISO 534

FACE

White woodfree uncoated paper, high whiteness and opacity

Substance	80gsm ± 4	ISO 536
Caliper	104µm ± 4	ISO 534

The product meets the European Toy Regulation EN 71/3

ADHESIVE

Water emulsion removable adhesive type, good short and long-term removability from most substrates including processed board, glass, steel and polyolefin films.

Peel adhesion	0.8 N/inch ± 0.2	FINAT1
Shear test	6h ± 2	FINAT8
Quick stick	0.7 N/inch ± 0.2	FINAT9
Min. application temp.	+5°C / +50°C	
Service temp. Range	-20°C/+60°C	

The product meets the European Toy Regulation EN71/3

BACKING

One-side coated white kraft, solventless silicon coated

Substance	85 gsm ± 3	ISO 536
Caliper	87 µm ± 5	ISO 534

The product meets the European Toy Regulation EN71/3

APPLICATIONS

All types of labels for industrial applications: information and product labelling.

NB. the removing properties are influenced by the kind of application surface. Trials are recommended, by the purchaser, prior to use, on the intended substrates. Not suitable for application on papers.

PRINTABILITY

Face: good printing results by all common print processes; suitable for laser and ink-jet printing
Backing: good printing results by all common print processes, in one or more colours.

SHELF LIFE AND USE

One (1) year from delivery date when stored at the following conditions:

- Temperature +5°C/+35°C
- Relative Humidity 45% - 60%
- Store in a cool dry place away from heaters or direct sunlight or rain
- Keep the sheets flat, the reels piled
- Store in the original packaging

All ITALSTICK products are subject to careful quality control throughout the production process and are warranted to be free from manufacturing defect and of quality. The reported information is based upon research and tests the Company believes to be reliable; such information does not constitute a warranty. The purchaser and/or user should carefully test, prior to use, suitability and performance of the product for the intended use and shall assume all risks for such use. ITALSTICK shall not be liable for damages beyond the replacement value of the defected product nor for incidental or consequential damages

All technical data are subject to change without prior notice.

ITALSTICK Soc. Coop.
via della Stazione, 6
I-41019 Soliera
www.italstick.com

Ph. +39 059 566705
Fax +39 059 565127
info@italstick.com